



# Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: CA20

Revision:

Product type: 503

Intended use: : To be used in walls and partitions, as an ancillary components for masonry  
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels  
Commerce way, Whitehall Industrial Estate  
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,  
Research and Environmental Applications (CEREA)  
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.  
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E <sub>k</sub> , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/360 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Material Coating reference L4h
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	242.0
Mass per unit area (kg/m <sup>2</sup> )	NPD
Mass (kg/m)	14.4
Load Ratio	65 - 100% Max load: 1:1 - 1:3 or <65% Max load 2:1 - 1:5

**hEN**

EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

**TableA1:**  
**Load bearing capacity**

Clear Opening span (mm)	SWL UDL (kN)
1500	55
1650	50.4
1800	46.6
1950	43.2
2100	40.3
2250	37.8
2400	35.6
2550	33.6
2700	31.9
2850	30.3
3000	28.8
3150	27.5
3300	26.3
3450	25.2
3600	24.2
3750	23.2
3900	21.5
4050	19.9
4200	18.5
4350	17.3
4500	16.1

**Note:**

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)