

Declaration of Performance

EU Regulation No 305/2011, Annex III

519

DOP Number: Product type:

Intended use: :

SC24 UNRESTRAINED

Revison: a

TableA1:

hEN

for

: 2012, Specification for ancillary components Part 2: Lintels

845 - 2 : masonary -

Z Ш

Load bearing capacity

To be used in walls and partitions, as an ancillar components for masonry (BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003. European Harmonised Standard EN 1090-1 :2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1:2009 The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above

standards. Factory Production Control Certificate GB16/871495 refers

Declared Performance:	
Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm
Nominal Height (mm)	235.0

NPD

11.5-12.8

-

Clear Opening SWL UDL (kN) span (mm) 600 28 28 750 900 21.4 1050 16.4 1200 13 1350 10.5 1500 8.7 1650 7.3 1800 6.2 1950 5.4 2100 4.7 2250 4.1 2400 3.6 2550 32 2700 2.9

Note:

Mass (kg/m)

Load Ratio

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.01.2025

Mass per unit area (kg/m²)

(Place and date of issue)

Michael Polley (General Manager)

Alley