



# Declaration of Performance

EU Regulation No 305/2011, Annex III

**DOP Number:** 529

**Revision:** a

**Product type:** SB21

**Intended use:** To be used in walls and partitions, as an ancillary components for masonry  
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

**Manufacturer:**

Harvey Steel Lintels  
Commerce way, Whitehall Industrial Estate  
Colchester, Essex CO2 8HH

**The Notified Testing Laboratory:**

University of Glamorgan Commercial Services Centre for Engineering,  
Research and Environmental Applications (CEREA)  
Llantwit Road, Treforest Pontypridd, CF37 1DL

**Assessment and Verification of Constancy of Performance:** System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003.  
European Harmonised Standard EN 1090-1 :2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1:2009  
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above standards. Factory Production Control Certificate GB16/871495 refers

**Declared Performance:**

Essential Characteristics	Performance
Load Bearing Capacity (E <sub>k</sub> , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	215.0
Mass per unit area (kg/m <sup>2</sup> )	NPD
Mass (kg/m)	15.9-26.9
Load Ratio	-

hEN  
EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

TableA1: Load bearing capacity	
Clear Opening span (mm)	SWL UDL (kN)
600	100.7
750	100.7
900	100.7
1050	100.7
1200	100.7
1350	100.7
1500	100.7
1650	100.7
1800	100.7
1950	93.7
2100	87.4
2250	82
2400	77.2
2550	72.9
2700	69
2850	65.6
3000	62.5
3150	58
3300	52.9
3450	48.4
3600	44.4
3750	40.9
3900	37.8
4050	35.1
4200	32.6
4350	30.4

**Note:**

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :  
Harvey Steel 01.01.2025  
(Place and date of issue)

Michael Polley (General Manager)