

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: OL14 Revison: Product type: 555 Intended use: : To be used in walls and partitions, as an ancillar components for masonry (BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure) Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate TableA1: Colchester, Essex CO2 8HH Load bearing capacity The Notified Testing Laboratory: Clear Opening SWL UDL University of Glamorgan Commercial Services Centre for Engineering, (kN) span (mm) Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL 600 750 Assessment and Verification of Constancy of Performance: System 3 900 This DOP is coverd by following harmonised standard: 1050 Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and 1200 fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003. 1350 The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 1500 1650 **Declared Performance:** 1800 **Essential Characteristics** Performance hEN 1950 Load Bearing Capacity (Ek, in kN) Given in TableA1 as safe working loads (SWL) under uniform distributed 2100 loading (UDL) 2250 for Deflection Under Load Less than effective span/360 as safe working load in service limit state 2400 : 2012, Specification for ancillary components Part 2: Lintels (EN 1990: 2002 + A1 ; 2005 NA) 2550 Water Absorption Zero 2700 Water Vapour Permeability Not Applicable 2850 Steel 64 W / m.k Thermal Resistance 3000 NPD (Contact Harvey steel for project specific details) document A Resistance to Fire 3150 Durability (against corrosion) Material Coating referrence L4h Resistant Durability (against freeze/thaw) **Dangerous Substance** None Minimum Bearing Length (mm) 150 mm Nominal Height (mm) 151.0 845 - 2 : masonary -Mass per unit area (kg/m²) NPD Mass (kg/m) 40 Z Load Ratio

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

David Harvey (Managing director)

5

4.9

3.6

2.8

22

1.8

(Place and date of issue)

(Signature)