

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: OL19 Revison:

Product type: 557

Intended use: To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics Performance Load Bearing Capacity (Ek, in kN) Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL) Deflection Under Load Less than effective span/360 as safe working load in service limit state (EN 1990: 2002 + A1; 2005 NA) Water Absorption Zero Water Vapour Permeability Not Applicable Thermal Resistance Steel 64 W / m.k NPD (Contact Harvey steel for project specific details) document A Resistance to Fire Material Coating referrence L4h Durability (against corrosion) Durability (against freeze/thaw) Resistant Dangerous Substance None Minimum Bearing Length (mm) 150 mm

Nominal Height (mm)	208.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	9.7
Load Ratio	-

hE	EN
omponents for	
845 - 2: 2012, Specification for ancillary components for	
2, Specification	Part 2: Lintels
845 - 2 : 2012	sonary - Part

Clear Opening SWL UDL		
SWL UDL (kN)		
26		
26		
26		
25.9		
20.4		
16.6		
13.7		
11.5		
9.8		
8.4		
7.4		
6.5		
5.7		
5.1		
4.6		

TableA1:

Load bearing capacity

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)