



# Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: OS3

Revision:

Product type: 574

Intended use: : To be used in walls and partitions, as an ancillary components for masonry  
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels  
Commerce way, Whitehall Industrial Estate  
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,  
Research and Environmental Applications (CEREA)  
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.  
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E <sub>k</sub> , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/360 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	0.0
Mass per unit area (kg/m <sup>2</sup> )	#DIV/0!
Mass (kg/m)	0.0
Load Ratio	0.0

**hEN**

EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

TableA1: Load bearing capacity	
Clear Opening span (mm)	SWL UDL (kN)
600	9
750	11.3
900	13.5
1050	12.5
1200	9.8
1350	8
1500	6.6
1650	5.7
1800	4.9
1950	4.3
2100	3.9
2250	3.5
2400	3.2
2550	2.9

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)