

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: OS4 Revison:

Product type: 575

<u>Intended use:</u>: To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate

Colchester, Essex CO2 8HH

<u>The Notified Testing Laboratory:</u>
University of Glamorgan Commercial Services Centre for Engineering,

Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/360 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	0.0
Mass per unit area (kg/m²)	#DIV/0!
Mass (kg/m)	0.0
Load Ratio	0.0

hE	ĒΝ
2 : 2012, Specification for ancillary components for	
illary comp	
on for anc	
Specification	rt 2: Lintels
45 - 2 : 2012, Specif	Pa
N 845 - 2	asonary - I

Clear Opening span (mm)	SWL UDL (kN)
600	21
750	26.3
900	26.3
1050	20.4
1200	15.8
1350	12.7
1500	10.5
1650	8.8
1800	7.6
1950	6.6
2100	5.8
2250	5.2
2400	4.7
2550	4.3
2700	3.9
2850	3.6
3000	3.4
3150	3.2
3300	3
<u> </u>	

TableA1:

Load bearing capacity

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)