Standard Straight Lintels

Customer S	Shipping Details	This f	orm is submitted as a (tick):	Request for quote:	An order:
Customer/Company:			Account Ref (if known):		
Contact Person:			Purchase order or Ref:		
Phone Number:					
Delivery Address:		Invoice address:			
_		_			
_					

	BASIC LINTEL INFORMATION			Typical lintel optional features		
Line	Lintel Specification	Length	QTY	Feature Brick height (or blank if not rqd.)	Outer Step Height (or blank if not rqd.)	Plaster Key? Y/N
1		mm		mm	mm	
2		mm		mm	mm	
3		mm		mm	mm	
4		mm		mm	mm	
5		mm		mm	mm	
6		mm		mm	mm	
7		mm		mm	mm	
8		mm		mm	mm	
9		mm		mm	mm	
10		mm		mm	mm	

Material Options	(tick one)	SKETCH & NOTES (if required)
LDX 2101 Stainless		
Grade 304 Stainless		
SS370 Stainless		
Other or Mix (specify in notes		
Hot Dip Galv. S275JR Mild Steel		
G600 Pre-Galv. S280 Mild Steel		
Other or Mix (specify in notes)		
Note: The safe working loads in this catalogue o apply to SS370 & LDX 2101®. Some lintels will f steel structural section regardless of material ch	eature a mild	We draw your lintel based on this information & send it to you for type & dimensional approval prior to manufacture as a final check.